

Series	Report	STC	OITC	Test Unit		
Number	Number	Rating	Rating	Width	Height	Glazing
SH-8100	RAL-TL08-207	27	22	47.250	59.250	7/8" I.G. (1/8" - 5/8" air space - 1/8")
SH-8100	RAL-TL08-206	32	29	47.250	59.250	7/8" I.G. (1/8" - 7/16" air space - 5/16"Lami. {1/8" - 0.090 PVB - 1/8"})
SH-8100	RAL-TL08-208	33	29	47.250	59.250	7/8" I.G. (3/16"Lami. {2/7mm - 0.060 PVB - 2.7mm} -5/16" air space - 5/16"Lami. {1/8" - 0.090 PVB - 1/8"})
SD-8700	FTL-6552	37	32	37.500	82.375	1" I.G. (3/6" - 7/16" air space - 7/16"Lami. {3/16" - 0.060 PVB - 3/16"})
PW-8150	FTL-6663	36	32	47.250	59.250	7/8" I.G. (3/16" - 3/8" air space - 5/16"Lami. {1/8" - 0.090 PVB - 1/8"})
PW-8300	FTL-6667	36	31	47.250	59.250	1" I.G. (3/16" - 1/2" air space - 5/16"Lami. {1/8" - 0.090 PVB - 1/8"})
SGD-8930	FTL-6675	33	25	72.000	80.000	1" I.G. (3/16" - 3/8" air space - 7/16"Lami. {3/16" - 0.105 PVB - 3/16"})
SGD-8940	FTL-6676	34	24	72.000	80.000	1" I.G. (3/16" - 3/8" air space - 7/16"Lami. {3/16" - 0.105 PVB - 3/16"})
HS-8200	FTL-7649	29	23	59.125	47.250	7/8" I.G. (1/8" - 5/8" air space - 1/8")
HS-8200	FTL-7650	32	26	59.125	47.250	7/8" I.G. (1/8" - 7/16" air space - 5/16"Lami. {1/8" - 0.090 PVB - 1/8"})
CA-8400	FTL-7645	31	25	23.625	59.125	7/8" I.G. (3/16" - 1/2" air space - 3/16")
CA-8400	FTL-7646	35	27	23.625	59.125	7/8" I.G. (1/8" - 7/16" air space - 5/16"Lami. {1/8" - 0.090 PVB - 1/8"})
AW-8450	FTL-7647	31	24	59.125	23.625	7/8" I.G. (3/16" - 1/2" air space - 3/16")
AW-8450	FTL-7648	35	26	59.125	23.625	7/8" I.G. (1/8" - 7/16" air space - 5/16"Lami. {1/8" - 0.090 PVB - 1/8"})
Legend:						
STC		Sound Transmission Class				
OITC		Outdoor-Indoor Trasmisison Class				