



WARNING: Do not use alcohol or ammonia based products, dishwashing detergents/soaps, products that contain abrasives, or other chemicals. Use of cleaning products and methods other than those specified below will damage the vinyl and void the warranty.

CAUTION: Remove jewelry or other objects that can puncture or cut the vinyl before cleaning your CWS Weather-Lite Windows & Doors.

- 1.** Do not wash panels when hot or in direct sunlight. Using a garden hose, with non-well water, gently hose off the exterior of the panels to remove loose dirt, dust, or debris. Clean the main frame and vinyl jamb tracks with a soft cloth and clean water.
- 2.** Starting with the bottom panel, raise approximately 2-3 inches, pull to the spring side and tilt the vinyl sash inward, removing it from the opening. Repeat for remaining vents.
- 3.** Clean each vent with a soft, lint free, clean cloth and rinse it with clean water. A cleaning solution such as Woolite® or Murphy Oil Soap® and warm water (one cap-full to one gallon water) will work nicely and protect your investment. Ensure the panel is dry and free of spots. Replace each vent in the same position as removed.
- 4.** Final clean your panels with CWS Vinyl Cleaner available from your CWS distributor. It will extend the life of your Weather-Lite Windows & Doors and reduce static electric charges that attract dust.

Thank you for choosing Custom Window Systems, Inc. and by following the simple steps above you will be able to enjoy your new Weather~Lite windows through many seasons.